

2006 SPECS



Dressta

New Dressta dozers feature increased drawbar pull, larger blades and improved operator controls. All TD-15M, TD-25M and TD-40E models include a left-handed joystick, which utilizes twin rocker switches and push buttons to allow selection of Hi or Lo geared track speeds, as well as transmission gears. By using the thumb and moving the joystick — rather than

manipulating three separate control levers — the operator gains complete machine motion functions over ground speeds and direction.

Dressta

Model	Net HP	Operating Weight (lbs.)	Drivetrain Type	Blade Capacity Range (cu. yds.)	Blade Width
TD-7M ^a	74	16,200-17,630	HydroDynamic	1.81-1.90	8' 7"-9' 3"
TD-7M DD ^a	74	16,200-17,630	Direct Drive	1.81-1.90	8' 7"-9' 3"
TD-8M ^b	85	17,360-18,100	HydroDynamic	1.9-2.2	8' 7"-9' 3"
TD-8M DD ^b	85	17,360-18,100	Direct Drive	1.9-2.2	8' 7"-9' 3"
TD-9M ^b	93	19,210-19,600	HydroDynamic	2.3-2.45	8' 10"-9' 3"
TD-9M DD ^b	93	19,210-19,600	Direct Drive	2.3-2.45	8' 10"-9' 3"
TD-10M ^b	101	19,395-19,645	HydroDynamic	2.66	9' 3"
TD-10M DD ^b	101	19,395-19,645	Direct Drive	2.66	9' 3"
TD-12C ^a	125	28,497	HydroDynamic	3.5-4.6	10' 2"-11' 2"
TD-12C DD ^a	125	28,497	Direct Drive	3.5-4.6	10' 2"-11' 2"
TD-12C XP ^b	142	32,866	HydroDynamic	3.5-4.6	10' 2"-11' 2"
TD-12C XP DD ^b	142	32,866	Direct Drive	3.5-4.6	10' 2"-11' 2"
TD-15M ^c	190	45,492-47,606	HydroDynamic	4.7-7.8	11' 3"-14' 8"
TD-20H ^a	225	52,337	HydroDynamic	6.8-8.10	11' 5"-13' 4"
TD-25M	320	79,829	HydroDynamic	27.5	18' 5"
TD-40E	520	146,915	HydroDynamic	52	22' 6"

a = Includes STD, LT and LGP versions; b = Includes STD and LGP versions; c = Includes STD, LT, LGP and WT versions